

The Secure Hash Algorithm Validation System (SHAVS)

March 1, 2004

Lawrence E. Bassham III

National Institute of Standards and Technology

Information Technology Laboratory

Computer Security Division

TABLE OF CONTENTS

1	INTRODUCTION.....	1
2	SCOPE.....	1
3	CONFORMANCE.....	1
4	DEFINITIONS, SYMBOLS, AND ABBREVIATIONS	2
4.1	DEFINITIONS.....	2
4.2	SYMBOLS.....	2
4.3	ABBREVIATIONS.....	2
5	DESIGN PHILOSOPHY OF THE SECURE HASH ALGORITHM VALIDATION SYSTEM	3
6	SHAVS TESTS.....	3
6.1	CONFIGURATION INFORMATION.....	3
6.2	THE SHORT MESSAGES TEST	4
6.2.1	The Short Messages Test for Bit-Oriented Implementations	4
6.2.2	The Short Messages Test for Byte-Oriented Implementations.....	5
6.3	THE SELECTED LONG MESSAGES TEST	6
6.3.1	The Selected Long Messages Test for Bit-Oriented Implementations	6
6.3.2	The Selected Long Messages Test for Byte-Oriented Implementations.....	7
6.4	THE PSEUDORANDOMLY GENERATED MESSAGES TEST	8
APPENDIX A	SAMPLES VALUES FOR SHA-1 TESTS.....	11
A.1	EXAMPLES OF THE SHORT MESSAGES TEST FOR SHA-1	11
A.2	EXAMPLES OF THE SELECTED LONG MESSAGES TEST FOR SHA-1.....	12
A.3	EXAMPLES OF THE PSEUDORANDOMLY GENERATED MESSAGES TEST FOR SHA-1.....	13
APPENDIX B	SAMPLE VALUES FOR SHA-224 TESTS.....	14
B.1	EXAMPLES OF THE SHORT MESSAGES TEST FOR SHA-224	14
B.2	EXAMPLES OF THE SELECTED LONG MESSAGES TEST FOR SHA-224.....	15
B.3	EXAMPLES OF THE PSEUDORANDOMLY GENERATED MESSAGES TEST FOR SHA-224.....	16
APPENDIX C	SAMPLE VALUES FOR SHA-256 TESTS.....	18
C.1	EXAMPLES OF THE SHORT MESSAGES TEST FOR SHA-256	18
C.2	EXAMPLES OF THE SELECTED LONG MESSAGES TEST FOR SHA-256.....	19
C.3	EXAMPLES OF THE PSEUDORANDOMLY GENERATED MESSAGES TEST FOR SHA-256.....	20
APPENDIX D	SAMPLE VALUES FOR SHA-384 TESTS.....	22
D.1	EXAMPLES OF THE SHORT MESSAGES TEST FOR SHA-384	22
D.2	EXAMPLES OF THE SELECTED LONG MESSAGES TEST FOR SHA-384.....	23
D.3	EXAMPLES OF THE PSEUDORANDOMLY GENERATED MESSAGES TEST FOR SHA-384.....	24
APPENDIX E	SAMPLE VALUES FOR SHA-512 TESTS.....	26
E.1	EXAMPLES OF THE SHORT MESSAGES TEST FOR SHA-512	26
E.2	EXAMPLES OF THE SELECTED LONG MESSAGES TEST FOR SHA-512.....	27

E.3	EXAMPLES OF THE PSEUDORANDOMLY GENERATED MESSAGES TEST FOR SHA-512.....	28
APPENDIX F	SAMPLE DATA FILES	31
F.1	SAMPLE <i>REQUEST</i> FILES.....	31
F.1.1	Sample SHA1ShortMsg.req.....	31
F.1.2	Sample SHA1LongMsg.req	32
F.1.3	Sample SHA1Monte.req.....	33
F.2	SAMPLE <i>FAX</i> FILES.....	33
F.2.1	Sample SHA1ShortMsg.fax.....	33
F.2.2	Sample SHA1LongMsg.fax.....	35
F.2.3	Sample SHA1Monte.fax.....	36
F.3	SAMPLE <i>SAMPLE</i> FILES.....	37
F.3.1	Sample SHA1ShortMsg.sam.....	37
F.3.2	Sample SHA1LongMsg.sam.....	38
F.3.3	Sample SHA1Monte.sam.....	39
F.4	SAMPLE <i>RESPONSE</i> FILES.....	40
F.4.1	Sample SHA1ShortMsg.rsp.....	40
F.2.2	Sample SHA1LongMsg.rsp	41
F.2.3	Sample SHA1Monte.rsp.....	43
APPENDIX G	REFERENCES	44

1 Introduction

This document, *The Secure Hash Algorithm Validation System (SHAVS)* specifies the procedures involved in validating implementations of the Secure Hash Algorithms in FIPS 180-2, *Secure Hash Standard (SHA-2)* [1]. The SHAVS is designed to perform automated testing on Implementations Under Test (IUTs). This document provides the basic design and configuration of the SHAVS. It includes the specifications for the three categories of tests that make up the SHAVS, i.e., the Short Messages Test, Long Messages Test, and Pseudorandomly Generated Messages Test. The requirements and administrative procedures specific to those seeking formal validation of an implementation of the Secure Hash Algorithm(s) are presented. The requirements described include the specific protocols for communication between the IUT and the SHAVS, the types of tests that the IUT must pass for formal validation, and general instructions for accessing and interfacing with the SHAVS. Several appendices with sample values for each of the tests are also provided. Additionally, an appendix with the format of the various input and output files of the tool is also provided.

2 Scope

This document specifies the tests required to validate IUTs for conformance to the Secure Hash Algorithm(s) as specified in [1]. When applied to IUTs that implement SHA, the SHAVS provides testing to determine the correctness of the algorithm implementation. In addition to determining conformance, the SHAVS is structured to detect implementation flaws including pointer problems, insufficient allocation of space, improper error handling, and incorrect behavior of the SHA implementation.

The SHAVS is composed of three types of validation tests, the Short Message Test, the Long Message Test, and the Pseudorandomly Generated Messages test. Additionally, the first two tests have an option to test bit-oriented or byte-oriented implementations. Byte-oriented implementations only hash messages with lengths divisible by 8, or integral bytes worth of data. Bit-oriented implementations can handle any length message (up to the limitation of the particular algorithm). While the specification for SHA specifies that messages up to at least $2^{64} - 1$ bits are possible, these tests only test messages up to a limited size of approximately 100,000 bits. This is adequate for detecting algorithmic and implementation errors.

3 Conformance

The successful completion of the tests contained within the SHAVS is required to claim conformance to FIPS 180-2. Testing for the cryptographic module in which the various algorithms specified in FIPS 180-2 is implemented is defined in FIPS PUB 140-2, *Security Requirements for Cryptographic Modules* [2].

4 Definitions, Symbols, and Abbreviations

4.1 Definitions

DEFINITION	MEANING
CMT laboratory	Cryptographic Module Testing laboratory that operates the DSAVS
Secure Hash Algorithm(s)	The algorithm(s) specified in FIPS 180-2, <i>Secure Hash Standard (SHS)</i> .

4.2 Symbols

SYMBOL	MEANING
L	The length of the message digest in bytes
Len	The length of a message in bits
l_{min}	Minimum message length for Selected Long Message Test
l_{max}	Maximum message length for Selected Long Message Test
m	Number of bits in the message block
MD	A Message Digest
Msg	A message
n	Number of bits in the message digest

4.3 Abbreviations

ABBREVIATION	MEANING
DEA	Data Encryption Algorithm
DSA	Digital Signature Algorithm specified in FIPS 186-2
DSAVS	Digital Signature Algorithm Validation System
IUT	Implementation Under Test

5 Design Philosophy Of The Secure Hash Algorithm Validation System

The SHAVS is designed to test conformance to SHA rather than provide a measure of a product's security. The validation tests are designed to assist in the detection of accidental implementation errors, and are not designed to detect intentional attempts to misrepresent conformance. Thus, validation should not be interpreted as an evaluation or endorsement of overall product security.

The SHAVS has the following design philosophy:

1. The SHAVS is designed to allow the testing of an IUT at locations remote to the SHAVS. The SHAVS and the IUT communicate data via *REQUEST* and *RESPONSE* files.
2. The testing performed within the SHAVS utilizes statistical sampling (i.e., only a small number of the possible cases are tested); hence, the successful validation of a device does not imply 100% conformance with the standard.

6 SHAVS Tests

The SHAVS for the Secure Hash Algorithm(s) consists of three types of tests: The Short Messages Test, The Long Messages Test, and The Pseudorandomly Generated Messages Test. The SHAVS provides conformance testing for the algorithm, as well as testing for apparent implementation errors. The IUT may be implemented in software, firmware, hardware, or any combination thereof.

An IUT may implement SHA in either of two modes. The first mode is the byte-oriented mode. In this mode the IUT only hashes messages that are an integral number of bytes in length; i.e., the length (in bits) of the message to be hashed is divisible by 8. The second mode is the bit-oriented mode. In this mode the IUT hashes messages of arbitrary length. Selecting the proper mode for an implementation will determine how the SHAVS tests will be performed. Both modes can be selected for the Short Messages Test and the Selected Long Messages Test. The Pseudorandomly Generated Messages Test is always run in byte-oriented mode.

6.1 Configuration Information

To initiate the validation process of the SHAVS, a vendor submits an application to an accredited laboratory requesting the validation of their implementation of SHA. The vendor's implementation is referred to as the Implementation Under Test (IUT). The request for validation includes background

information describing the IUT along with information needed by the SHAVS to perform the specific tests. More specifically, the request for validation should include:

1. Vendor Name;
2. Product Name;
3. Product Version;
4. Implementation in software, firmware, or hardware;
5. Processor and Operating System with which the IUT was tested if the IUT is implemented in software or firmware;
6. Brief description of the IUT or the product/product family in which the IUT is implemented by the vendor (2-3 sentences); and

Whether the IUT handles bit-oriented messages or only byte-oriented messages.

6.2 The Short Messages Test

An implementation of SHA must be able to correctly generate message digests for messages of arbitrary length. The SHAVS tests this property by supplying the IUT with a number of short messages. The Short Messages Test has two versions, one for bit-oriented implementations and another for byte-oriented implementations.

6.2.1 The Short Messages Test for Bit-Oriented Implementations

This test generates a number of short messages equal to the number of bits in the hash block plus one. For example, SHA-1 defines a block length of $m=512$ bits. Therefore, for testing SHA-1, 513 unpredictable messages will be generated with lengths from 0 to 512 bits.

The SHAVS:

- A. Generates $m + 1$ messages of length 0 to m .
- B. Creates a *REQUEST* file (Filename: <Alg>ShortMsg.req) containing:
 1. The Product Information (vendor, product name, version); and
 2. The sequence of $m + 1$ messages to be hashed.

Note: The CMT laboratory sends the *REQUEST* file to the IUT.

- C. Creates a *FAX* file (Filename: <Alg>ShortMsg.fax) containing:
 1. The Product Name; and
 2. The $m + 1$ datasets containing:

- a. The messages, and
- b. The message digest of the message.

Note: The CMT laboratory retains the *FAX* file.

The IUT:

- A. Generates message digests using the messages supplied by the SHAVS in the *REQUEST* file.
- B. Creates a *RESPONSE* file (Filename: <Alg>ShortMsg.rsp) containing:
 - 1. The Product Name; and
 - 2. The $m + 1$ datasets containing:
 - a. The messages, and
 - b. The message digest of the messages.

Note: The IUT sends the *RESPONSE* file to the SHAVS.

The SHAVS:

- A. Compares the *RESPONSE* file with the *FAX* file. For each message, the SHAVS verifies that the IUT generated the correct message digest.
- B. If all message digests generated by the IUT are correct, records PASS for this test; otherwise, records FAIL.

6.2.2 The Short Messages Test for Byte-Oriented Implementations

This test generates a number of short messages equal to the number of bytes in the hash block plus one. For example, SHA-1 defines a block length of $m=512$ bits resulting in a block size of 64 bytes. Therefore, for testing SHA-1, 65 unpredictable messages will be generated with lengths of 0, 8, 16, ..., 512 bits.

The SHAVS:

- A. Generates $m/8 + 1$ messages of length 0, 8, 16, ..., m .
- B. Creates a *REQUEST* file (Filename: <Alg>ShortMsg.req) containing:
 - 1. The Product Name; and
 - 2. The sequence of $m/8 + 1$ messages to be hashed.

Note: The CMT laboratory sends the *REQUEST* file to the IUT.
- C. Creates a *FAX* file (Filename: <Alg>ShortMsg.fax) containing:
 - 1. The Product Name; and

2. The $m/8 + 1$ datasets containing:
 - a. The message, and
 - b. The message digest of the message.

Note: The CMT laboratory retains the *FAX* file.

The IUT:

- A. Generates message digests using the messages supplied by the SHAVS in the *REQUEST* file.
- B. Creates a *RESPONSE* file (Filename: <Alg>ShortMsg.rsp) containing:
 1. The Product Name; and
 2. The $m/8 + 1$ datasets containing:
 - a. The message, and
 - b. The message digest of the message.

Note: The IUT sends the *RESPONSE* file to the SHAVS.

The SHAVS:

- A. Compares the *RESPONSE* file with the *FAX* file. For each message, the SHAVS verifies that the IUT generated the correct message digest.
- B. If all message digests generated by the IUT are correct, records PASS for this test; otherwise, records FAIL.

6.3 The Selected Long Messages Test

An implementation of SHA must be able to correctly generate message digests for messages that span multiple message blocks. The SHAVS tests this property by supplying selected unpredictable long messages to the IUT. The IUT then generates message digests for each message. The Selected Long Messages Test has two versions, one for bit-oriented implementations and another for byte-oriented implementations.

6.3.1 The Selected Long Messages Test for Bit-Oriented Implementations

This test generates a number of long messages equal to the number of bits in the hash block, m . These message range in size from $m+99 \leq len \leq m*100$. For example, SHA-1 defines a block length of $m=512$ bits. Therefore, for testing SHA-1, 512 unpredictable long messages will be generated with lengths (in bits) of:

$$512 + 99*i, 1 \leq i \leq 512.$$

The SHAVS:

- A. Generates m messages of the length specified above.

B. Creates a *REQUEST* file (Filename: <Alg>LongMsg.req) containing:

1. The Product Name; and
2. The sequence of m messages to be hashed.

Note: The CMT laboratory sends the *REQUEST* file to the IUT.

C. Creates a *FAX* file (Filename: <Alg>LongMsg.fax) containing:

1. The Product Name; and
2. The m datasets containing:
 - a. The message, and
 - b. The message digest of the message.

Note: The CMT laboratory retains the *FAX* file at the SHAVS.

The IUT:

A. Generates message digests using the messages supplied by the SHAVS in the *REQUEST* file.

B. Creates a *RESPONSE* file (Filename: <Alg>LongMsg.rsp) containing:

1. The Product Name; and
2. The m datasets containing:
 - a. The message, and
 - b. The message digest of the message.

Note: The IUT sends the *RESPONSE* file to the SHAVS.

The SHAVS:

A. Compares the *RESPONSE* file with the *FAX* file. For each message, the SHAVS verifies that the IUT generated the correct message digest.

B. If all message digests generated by the IUT are correct, records PASS for this test; otherwise, records FAIL.

6.3.2 The Selected Long Messages Test for Byte-Oriented Implementations

This test generates a number of long messages equal to the number of bytes in the hash block, $m/8$. These message range in size from $m+99 \leq len \leq m*100$. For example, SHA-1 defines a block length of $m/8 = 64$ bytes. Therefore, for testing SHA-1, 64 unpredictable long messages will be generated with lengths (in bits) of:

$$512 + 8*99*i, 1 \leq i \leq 64.$$

The SHAVS:

- A. Generates $m/8$ messages of the length specified above.
- B. Creates a *REQUEST* file (Filename: LongMsg.req) containing:
 - 1. The Product Information (vendor, product name, version); and
 - 2. The sequence of $m/8$ messages to be hashed.

Note: The CMT laboratory sends the *REQUEST* file to the IUT.

- C. Creates a *FAX* file (Filename: LongMsg.fax) containing:
 - 1. The Product Information (vendor, product name, version); and
 - 2. The $m/8$ datasets containing:
 - a. The message, and
 - b. The message digest of the message.

Note: The CMT laboratory retains the *FAX* file.

The IUT:

- A. Generates message digests using the message supplied by the SHAVS in the *REQUEST* file.
- B. Creates a *RESPONSE* file (Filename: LongMsg.rsp) containing:
 - 1. The Product Information (vendor, product name, version); and
 - 2. The $m/8$ datasets containing:
 - a. The message, and
 - b. The message digest of the message.

Note: The IUT sends the *RESPONSE* file to the SHAVS.

The SHAVS:

- A. Compares the *RESPONSE* file with the *FAX* file. For each message, the SHAVS verifies that the IUT generated the correct message digest.
 - B. If all message digests generated by the IUT are correct, records PASS for this test; otherwise, records FAIL.

6.4 The Pseudorandomly Generated Messages Test

The SHAVS tests the correctness of message digests generated from pseudorandomly generated messages by supplying a seed, *Seed*, of length n bits. This seed is used by a pseudorandom function to generate 100,000 message digests. 100 of the 100,000 message digests, once every 1,000 hashes, are recorded as checkpoints to the operation of the generator. The IUT uses the same procedure to

generate the same 100,000 message digests and 100 checkpoint values. The SHAVS compares each

```

INPUT: Seed - A random seed  $n$  bits long
{
    for (j=0; j<100; j++) {
        MD0 = MD1 = MD2 = Seed;
        for (i=3; i<1003; i++) {
            Mi = MDi-3 || MDi-2 || MDi-1;
            MDi = SHA(Mi);
        }
        MDj = Seed = MDi;
        OUTPUT: MDj
    }
}

```

of the recorded 100 message digests with those generated by the IUT.

The procedure used to generate the 100 checkpoint messages digest is as follows:

- 1) 100,000 pseudorandom messages are generated by using previous message digests as the input to the hash algorithm; and,
- 2) After every 1,000 hashes a sample is taken and is provided as a checkpoint. These checkpoints are denoted MD_j in Figure 1.

Figure 1: Code for Generating Pseudorandom Messages

The SHAVS:

- A. Generates a seed, *Seed*, of length n bits.
- B. Creates a *REQUEST* file (Filename: Monte.req) containing:
 1. The Product Information (vendor, product name, version); and
 2. The *Seed*.

Note: The CMT laboratory sends the *REQUEST* file to the IUT.

- C. Creates a *FAX* file (Filename: Monte.fax) containing:
 1. The Product Information (vendor, product name, version);
 2. The *Seed*; and
 3. The 100 message digests, MD_j , from Figure 1.

Note: The CMT laboratory retains the *FAX* file at the SHAVS.

The IUT:

- A. Generates the 100 message digest using the *Seed* supplied by the SHAVS in the *REQUEST* file.
- B. Creates a *RESPONSE* file (Filename: Monte.rsp) containing:
 - 1. The Product Information (vendor, product name, version);
 - 2. The *Seed*; and
 - 3. The 100 message digest MD_j from Figure 1.

Note: The IUT sends the *RESPONSE* file to the SHAVS.

The SHAVS:

- A. Compares the *RESPONSE* file with the *FAX* file. The SHAVS verifies that the IUT generated the correct message digests.
- B. If all message digests generated by the IUT are correct, records PASS for this test; otherwise, records FAIL.

Appendix A Samples Values for SHA-1 Tests

Each example contains the length of the sample message that is to be hashed, the hex representation of the message, *M*, and the message digest, *MD*, of the message using SHA-1. For bit-oriented messages, the message is in the most significant digits of the hex representation. In Example 1 below, the binary representation of the 5-bit message 98 is 10011.

A.1 Examples Of The Short Messages Test for SHA-1

Example 1:

Length: 5
M: 98
MD: 29826b00 3b906e66 0eff4027 ce98af35 31ac75ba

Example 2:

Length: 8
M: 5e
MD: 5e6f80a3 4a9798ca fc6a5db9 6cc57ba4 c4db59c2

Example 3:

Length: 123
M: 49b2aec2 594bbe3a 3b117542 d94ac880
MD: 6239781e 03729919 c01955b3 ffa8acb6 0b988340

Example 4:

Length: 128
M: 9a7dfdf1 ecead06e d646aa55 fe757146
MD: 82abff66 05dbe1c1 7def12a3 94fa22a8 2b544a35

A.2 Examples Of The Selected Long Messages Test for SHA-1

Example 1:

Length: 611

M: 65f93299 5ba4ce2c b1b4a2e7 1ae70220 aacec896
2dd4499c
bd7c887a 94eaaa10 1ea5aabc 529b4e7e 43665a5a
f2cd03fe
678ea6a5 005bba3b 082204c2 8b9109f4 69dac92a
aab3aa7c
11a1b32a e0

MD: 8c5b2a5d dae5a97f c7f9d856 61c672ad bf7933d4

Example 2:

Length: 1304

M: f78f9214 1bcd170a e89b4fba 15a1d59f 3fd84d22
3c9251bd
acbbae61 d05ed115 a06a7ce1 17b7beea d24421de
d9c32592
bd57edea e39c39fa 1fe8946a 84d0cf1f 7beead17
13e2e095
9897347f 67c80b04 00c20981 5d6b10a6 83836fd5
562a56ca
b1a28e81 b6576654 631cf165 66b86e3b 33a108b0
5307c00a
ff14a768 ed735060 6a0f85e6 a91d396f 5b5cbe57
7f9b3880
7c7d523d 6d792f6e bc24a4ec f2b3a427 cdbbfb

MD: cb0082c8 f197d260 991ba6a4 60e76e20 2bad27b3

A.3 Examples of The Pseudorandomly Generated Messages Test for SHA-1

A sample seed for this routine is the following string:

Seed: d0569cb3 665a8a43 eb6ea23d 75a3c4d2 054a0d7d

The first few messages, M_i , and hashes, MD_i , contained in the inner loop of the routine in Figure 1 are:

$M_{i=3}$:	d0569cb3	665a8a43	eb6ea23d	75a3c4d2	054a0d7d
	d0569cb3	665a8a43	eb6ea23d	75a3c4d2	054a0d7d
	d0569cb3	665a8a43	eb6ea23d	75a3c4d2	054a0d7d
$MD_{i=3}$:	5c1f6ab1	dd1a1b92	313ef55b	d94e5d90	eee5fd42
$M_{i=4}$:	d0569cb3	665a8a43	eb6ea23d	75a3c4d2	054a0d7d
	d0569cb3	665a8a43	eb6ea23d	75a3c4d2	054a0d7d
	5c1f6ab1	dd1a1b92	313ef55b	d94e5d90	eee5fd42
$MD_{i=4}$:	3dc3b220	871bb348	8a66c39d	ea577c2d	1ce40168
$M_{i=5}$:	d0569cb3	665a8a43	eb6ea23d	75a3c4d2	054a0d7d
	5c1f6ab1	dd1a1b92	313ef55b	d94e5d90	eee5fd42
	3dc3b220	871bb348	8a66c39d	ea577c2d	1ce40168
$MD_{i=5}$:	dd4b2577	7737c82c	f228ac14	cf04b905	b081ac72
$M_{i=6}$:	5c1f6ab1	dd1a1b92	313ef55b	d94e5d90	eee5fd42
	3dc3b220	871bb348	8a66c39d	ea577c2d	1ce40168
	dd4b2577	7737c82c	f228ac14	cf04b905	b081ac72
$MD_{i=6}$:	129aef9d	88d256d5	a667637e	a215d7d8	4d710156

The first few message digests, MD_j , that are the output of the routine found in Figure 1 are:

$MD_{j=0}$:	e2168368	19477c7f	78e0d843	fe4ff1b6	d6c14cd4
$MD_{j=1}$:	a2dbc7a5	b1c6c0a8	bc7b7aaa	41252a6a	7d0690dbc
$MD_{j=2}$:	db1f9050	bb863dfe	f4ce3718	6044e2ee	b17ee013
$MD_{j=3}$:	127fdedf	43d372a5	1d5747c4	8fbffe38	ef6cdf7b

Appendix B Sample Values for SHA-224 Tests

Each example contains the length of the sample message that is to be hashed, the hex representation of the message, *M*, and the message digest, *MD*, of the message using SHA-224. For bit-oriented messages, the message is in the most significant digits of the hex representation. In Example 1 below, the binary representation of the 5-bit message 68 is 01101.

B.1 Examples Of The Short Messages Test for SHA-224

Example 1:

Length: 5
M: 68
MD: e3b04855 2c3c387b cab37f6e b06bb79b
96a4aee5 ff27f515 31a9551c

Example 2:

Length: 8
M: 07
MD: 00ecd5f1 38422b8a d74c9799 fd826c53
1bad2fca bc7450be e2aa8c2a

Example 3:

Length: 123
M: f07006f2 5a0bea68 cd76a295 87c28da0
MD: 1b01db6c b4a9e43d ed1516be b3db0b87
b6d1ea43 187462c6 08137150

Example 4:

Length: 128
M: 18804005 dd4fbd15 56299d6f 9d93df62
MD: df90d78a a78821c9 9b40ba4c 966921ac
cd8ffb1e 98ac388e 56191db1

B.2 Examples Of The Selected Long Messages Test for SHA-224

Example 1:

Length: 611

M: a2be6e46 32810902 94d9ce94 82656942 3a3a305e
d5e2116c d4a4c987 fc065700 6491b149 ccd4b511
30ac62b1 9dc248c7 44543d20 cd3952dc ed1f06cc
3b18b91f 3f55633e cc3085f4 907060d2 e0

MD: 54bea6ea b8195a2e b0a7906a 4b4a8766
66300eef bd1f3b84 74f9cd57

Example 2:

Length: 1304

M: 55b21007 9c61b53a dd520622 d1ac97d5 cdbe8cb3
3aa0ae34 4517bee4 d7ba09ab c8533c52 50887a43
bebbac90 6c2e1837 f26b36a5 9ae3be78 14d50689
6b718b2a 383ecdac 16b96125 553f416f f32c6674
c74599a9 005386d9 ce111224 5f48ee47 0d396c1e
d63b9267 0ca56ec8 4deea814 b6135eca 54392bde
db9489bc 9b875a8b af0dc1ae 78573691 4ab7daa2
64bc079d 269f2c0d 7eddd810 a426145a 0776f67c 878273

MD: 0b31894e c8937ad9 b91bdfbc ba294d9a
defaa18e 09305e9f 20d5c3a4

B.3 Examples of The Pseudorandomly Generated Messages Test for SHA-224

A sample seed for this routine is the following string:

Seed: d0569cb3 665a8a43 eb6ea23d 75a3c4d2
 054a0d7d 66a9ca99 c9ceb027

The first few messages, M_i , and hashes, MD_i , contained in the inner loop of the routine in Figure 1 are:

$M_{i=3}$: d0569cb3 665a8a43 eb6ea23d 75a3c4d2 054a0d7d
 66a9ca99 c9ceb027 d0569cb3 665a8a43 eb6ea23d
 75a3c4d2 054a0d7d 66a9ca99 c9ceb027 d0569cb3
 665a8a43 eb6ea23d 75a3c4d2 054a0d7d 66a9ca99
 c9ceb027

$MD_{i=3}$: 38cea69d 7be80c14 ab3becb1 e02e7b67
 ced60a05 1c4a0100 e3e613b4

$M_{i=4}$: d0569cb3 665a8a43 eb6ea23d 75a3c4d2 054a0d7d
 66a9ca99 c9ceb027 d0569cb3 665a8a43 eb6ea23d
 75a3c4d2 054a0d7d 66a9ca99 c9ceb027 38cea69d
 7be80c14 ab3becb1 e02e7b67 ced60a05 1c4a0100
 e3e613b4

$MD_{i=4}$: ee210ffc 8db91566 6c2a4fcb 37d9e5c5
 8993c01b dccf706a 4077f955

$M_{i=5}$: d0569cb3 665a8a43 eb6ea23d 75a3c4d2 054a0d7d
 66a9ca99 c9ceb027 38cea69d 7be80c14 ab3becb1
 e02e7b67 ced60a05 1c4a0100 e3e613b4 ee210ffc
 8db91566 6c2a4fcb 37d9e5c5 8993c01b dccf706a
 4077f955

$MD_{i=5}$: 915eb09c 83e58cb8 ed11d8f4 bb361798
 42146256 08de7de8 dcab4030

$M_{i=6}$: 38cea69d 7be80c14 ab3becb1 e02e7b67 ced60a05
 1c4a0100 e3e613b4 ee210ffc 8db91566 6c2a4fcb
 37d9e5c5 8993c01b dccf706a 4077f955 915eb09c
 83e58cb8 ed11d8f4 bb361798 42146256 08de7de8
 dcab4030

$MD_{i=6}$: 25867f03 8cfcf093 4c575ba5 67bb23a4
 40e0fab9 84afbe23 a5e26b3b

The first few message digests, MD_j , that are the output of the routine found in Figure 1 are:

```
MDj=0:    100966a5 b4fde0b4 2e2a6c59 53d4d7f4
           1ba7cf79 fd2df431 416734be

MDj=1:    1dca396b 0c417715 defaae96 41e10a2e
           99d55abc b8a00061 eb3be8bd

MDj=2:    1864e627 bdb23199 73cd5ed7 d68da71d
           8bf0f983 d8d9ab32 c34adb34

MDj=3:    a2406481 fc1bcaf2 4dd08e67 52e84470
           9563fb91 6227fed5 98eb621f
```

Appendix C Sample Values for SHA-256 Tests

Each example contains the length of the sample message that is to be hashed, the hex representation of the message, *M*, and the message digest, *MD*, of the message using SHA-256. For bit-oriented messages, the message is in the most significant digits of the hex representation. In Example 1 below, the binary representation of the 5-bit message 68 is 01101.

C.1 Examples Of The Short Messages Test for SHA-256

Example 1:

Length: 5
M: 68
MD: d6d3e02a 31a84a8c aa9718ed 6c2057be
09db45e7 823eb507 9ce7a573 a3760f95

Example 2:

Length: 8
M: 19
MD: 68aa2e2e e5dff96e 3355e6c7 ee373e3d
6a4e17f7 5f9518d8 43709c0c 9bc3e3d4

Example 3:

Length: 123
M: be2746c6 db52765f db2f8870 0f9a7360
MD: 77ec1dc8 9c821ff2 a1279089 fa091b35
b8cd960b caf7de01 c6a76807 56beb972

Example 4:

Length: 128
M: e3d72570 dcdd787c e3887ab2 cd684652
MD: 175ee69b 02ba9b58 e2b0a5fd 13819cea
573f3940 a94f8251 28cf4209 beabb4e8

C.2 Examples Of The Selected Long Messages Test for SHA-256

Example 1:

Length: 611

M: 3e740371 c810c2b9 9fc04e80 4907ef7c f26be28b
57cb58a3 e2f3c007 166e49c1 2e9ba34c 01040691
29ea7615 64254570 3a2bd901 e16eb0e0 5deba014
ebff6406 a07d5436 4eff742d a779b0b3 a0

MD: 3e9ad646 8bbbad2a c3c2cdc2 92e018ba
5fd70b96 0cf16797 77fce708 fdb066e9

Example 2:

Length: 1304

M: 8326754e 2277372f 4fc12b20 527afef0 4d8a0569
71b11ad5 7123a7c1 37760000 d7bef6f3 c1f7a908
3aa39d81 0db31077 7dab8b1e 7f02b84a 26c77332
5f8b2374 de7a4b5a 58cb5c5c f35bcee6 fb946e5b
d694fa59 3a8beb3f 9d6592ec edaa66ca 82a29d0c
51bcf933 6230e5d7 84e4c0a4 3f8d79a3 0a165cba
be452b77 4b9c7109 a97d138f 12922896 6f6c0adc
106aad5a 9fdd3082 5769b2c6 71af6759 df28eb39
3d54d6

MD: 97dbca7d f46d62c8 a422c941 dd7e835b
8ad33617 63f7e9b2 d95f4f0d a6e1ccbc

C.3 Examples of The Pseudorandomly Generated Messages Test for SHA-256

A sample seed for this routine is the following string:

Seed: f41ece26 13e45739 15696b5a dcd51ca3
 28be3bf5 66a9ca99 c9ceb027 9c1cb0a7

The first few messages, M_i , and hashes, MD_i , contained in the inner loop of the routine in Figure 1 are:

$M_{i=3}$: f41ece26 13e45739 15696b5a dcd51ca3 28be3bf5
 66a9ca99 c9ceb027 9c1cb0a7 f41ece26 13e45739
 15696b5a dcd51ca3 28be3bf5 66a9ca99 c9ceb027
 9c1cb0a7 f41ece26 13e45739 15696b5a dcd51ca3
 28be3bf5 66a9ca99 c9ceb027 9c1cb0a7

$MD_{i=3}$: fddf1b37 dd34b3b2 01d43c57 bcde1158
 38f0df70 1da93c3b f2c9c868 96e7e6c7

$M_{i=4}$: f41ece26 13e45739 15696b5a dcd51ca3 28be3bf5
 66a9ca99 c9ceb027 9c1cb0a7 f41ece26 13e45739
 15696b5a dcd51ca3 28be3bf5 66a9ca99 c9ceb027
 9c1cb0a7 fddf1b37 dd34b3b2 01d43c57 bcde1158
 38f0df70 1da93c3b f2c9c868 96e7e6c7

$MD_{i=4}$: 3b9e2613 dc71d499 25cc3258 a3a4201a
 ea4336c2 a648ca8d ffb45bbd ad4835e8

$M_{i=5}$: f41ece26 13e45739 15696b5a dcd51ca3 28be3bf5
 66a9ca99 c9ceb027 9c1cb0a7 fddf1b37 dd34b3b2
 01d43c57 bcde1158 38f0df70 1da93c3b f2c9c868
 96e7e6c7 3b9e2613 dc71d499 25cc3258 a3a4201a
 ea4336c2 a648ca8d ffb45bbd ad4835e8

$MD_{i=5}$: 9fbac41c 7453a2c8 8fd3fed1 f685ef27
 587bebcc 573209bc c1b9f9ee cf03c1fd

$M_{i=6}$: fddf1b37 dd34b3b2 01d43c57 bcde1158 38f0df70
 1da93c3b f2c9c868 96e7e6c7 3b9e2613 dc71d499
 25cc3258 a3a4201a ea4336c2 a648ca8d ffb45bbd
 ad4835e8 9fbac41c 7453a2c8 8fd3fed1 f685ef27
 587bebcc 573209bc c1b9f9ee cf03c1fd

$MD_{i=6}$: b125c98b 1a9d25f3 37b5a788 15b6b7a7
 f091d328 80e8681b dec8584b 92aa3bf8

The first few message digests, MD_j , that are the output of the routine found in Figure 1 are:

$MD_{j=0}:$	83d28614	d49c3adc	1d6fc05d	b5f48037
	c056f8d2	a4ce44ec	6457dea5	dd797cd1
$MD_{j=1}:$	99dbe312	7ef2e93d	d9322d6a	07909eb3
	3b63995e	529b3f95	4b858162	1bb74d39
$MD_{j=2}:$	8d4be295	bb64661c	a3c7efd1	29a2f725
	b33072db	dde32385	b9a87b9a	f88ea76f
$MD_{j=3}:$	40af5d3f	9716b040	df9408e3	1536b70f
	f906ec51	b00447ca	97d7dd97	c12411f4

Appendix D Sample Values for SHA-384 Tests

Each example contains the length of the sample message that is to be hashed, the hex representation of the message, *M*, and the message digest, *MD*, of the message using SHA-384. For bit-oriented messages, the message is in the most significant digits of the hex representation. In Example 1 below, the binary representation of the 5-bit message 10 is 10000.

D.1 Examples Of The Short Messages Test for SHA-384

Example 1:

Length: 5
M: 10
MD: 8d17be79 e32b6718 e07d8a60 3eb84ba0 478f7fcf
d1bb9399 5f7d1149 e09143ac 1ffcfc56 820e469f
3878d957 a15a3fe4

Example 2:

Length: 8
M: b9
MD: bc8089a1 9007c0b1 4195f4ec c74094fe c64f01f9
0929282c 2fb39288 1578208a d466828b 1c6c283d
2722cf0a d1ab6938

Example 3:

Length: 123
M: 8bc500c7 7ceed987 9da98910 7ce0aaa0
MD: d8c43b38 e12e7c42 a7c9b810 299fd6a7 70bef309
20f17532 a898de62 c7a07e42 93449c0b 5fa70109
f0783211 cfc4bce3

Example 4:

Length: 128
M: a41c4977 79c0375f f10a7f4e 08591739
MD: c9a68443 a0058122 56b8ec76 b00516f0 dbb74fab
26d66591 3f194b6f fb0e91ea 9967566b 58109cbc
675cc208 e4c823f7

D.2 Examples Of The Selected Long Messages Test for SHA-384

Example 1:

Length: 1123

M: 68f50179 2dea9796 767022d9 3da71679 309920fa
1012aea3 57b2b133 1d40a1d0 3c41c240 b3c9a75b
4892f4c0 724b68c8 75321ab8 cfe5023b d375bc0f
94bd89fe 04f29710 5d7b82ff c0021aeb 1ccb674f
5244ea34 97de26a4 191c5f62 e5e9a2d8 082f0551
f4a53068 26e91cc0 06ce1bf6 0ff719d4 2fa521c8
71cd2394 d96ef446 8f21966b 41f2ba80 c26e83a9
e0

MD: 5860e8de 91c21578 bb4174d2 27898a98 e0b45c4c
760f0095 49495614 daedc077 5d92d11d 9f8ce9b0
64eeac8d afc3a297

Example 2:

Length: 1816

M: 399669e2 8f6b9c6d bcbb6912 ec10ffcf 74790349
b7dc8fbe 4a8e7b3b 5621db0f 3e7dc87f 823264bb
e40d1811 c9ea2061 e1c84ad1 0a23fac1 727e7202
fc3f5042 e6bf58cb a8a2746e 1f64f9b9 ea352c71
1507053c f4e5339d 52865f25 cc22b5e8 7784a12f
c961d66c b6e89573 199a2ce6 565cbdf1 3dca4038
32cfcb0e 8b7211e8 3af32a11 ac17929f f1c073a5
1cc027aa edeff85a ad7c2b7c 5a803e24 04d96d2a
77357bda 1a6daeed 17151cb9 bc5125a4 22e941de
0ca0fc50 11c23ecf fefdd096 76711cf3 db0a3440
720e1615 c1f22fbc 3c721de5 21e1b99b a1bd5577
40864214 7ed096

MD: 4f440db1 e6edd289 9fa335f0 9515aa02 5ee177a7
9f4b4aaf 38e42b5c 4de660f5 de8fb2a5 b2fbd2a3
cbffd20c ff1288c0

D.3 Examples of The Pseudorandomly Generated Messages Test for SHA-384

A sample seed for this routine is the following string:

Seed: 8240bc51 e4ec7ef7 6d18e352 04a19f51 a5213a73
 a81d6f94 4680d307 5948b7e4 63804ea3 d26e13ea
 820d65a4 84be7453

The first few messages, M_i , and hashes, MD_i , contained in the inner loop of the routine in Figure 1 are:

$M_{i=3}$: 8240bc51 e4ec7ef7 6d18e352 04a19f51 a5213a73
 a81d6f94 4680d307 5948b7e4 63804ea3 d26e13ea
 820d65a4 84be7453 8240bc51 e4ec7ef7 6d18e352
 04a19f51 a5213a73 a81d6f94 4680d307 5948b7e4
 63804ea3 d26e13ea 820d65a4 84be7453 8240bc51
 e4ec7ef7 6d18e352 04a19f51 a5213a73 a81d6f94
 4680d307 5948b7e4 63804ea3 d26e13ea 820d65a4
 84be7453

$MD_{i=3}$: 8ff53918 fb4da556 6f074f64 1f2ce018 a688fcbc
 b2efdb13 ba6b3578 bcd5a489 8d0b2d88 702dbbd8
 310bea5a 975adf20

$M_{i=4}$: 8240bc51 e4ec7ef7 6d18e352 04a19f51 a5213a73
 a81d6f94 4680d307 5948b7e4 63804ea3 d26e13ea
 820d65a4 84be7453 8240bc51 e4ec7ef7 6d18e352
 04a19f51 a5213a73 a81d6f94 4680d307 5948b7e4
 63804ea3 d26e13ea 820d65a4 84be7453 8ff53918
 fb4da556 6f074f64 1f2ce018 a688fcbc b2efdb13
 ba6b3578 bcd5a489 8d0b2d88 702dbbd8 310bea5a
 975adf20

$MD_{i=4}$: b5d6eb75 ae9bd90a 27e46f0d 732b53bc b74b8ff2
 f5df4d53 4ea78e8d beb31273 78bfafb1 35d59ec5
 3d1f15f7 c839cfaf

$M_{i=5}$: 8240bc51 e4ec7ef7 6d18e352 04a19f51 a5213a73
 a81d6f94 4680d307 5948b7e4 63804ea3 d26e13ea
 820d65a4 84be7453 8ff53918 fb4da556 6f074f64
 1f2ce018 a688fcbc b2efdb13 ba6b3578 bcd5a489
 8d0b2d88 702dbbd8 310bea5a 975adf20 b5d6eb75
 ae9bd90a 27e46f0d 732b53bc b74b8ff2 f5df4d53
 4ea78e8d beb31273 78bfafb1 35d59ec5 3d1f15f7
 c839cfaf

$MD_{i=5}:$	7870a434	da5d941c	4cdde45a	de8e4fd1	178ea3d3
	6ecd1231	fe675eb9	a5e61c01	34e495ba	2a4c3b11
	1a861abc	679f9a37			

$M_{i=6}:$	8ff53918	fb4da556	6f074f64	1f2ce018	a688fcbb
	b2efdb13	ba6b3578	bcd5a489	8d0b2d88	702dbbd8
	310bea5a	975adf20	b5d6eb75	ae9bd90a	27e46f0d
	732b53bc	b74b8ff2	f5df4d53	4ea78e8d	beb31273
	78bfafb1	35d59ec5	3d1f15f7	c839cfaf	7870a434
	da5d941c	4cdde45a	de8e4fd1	178ea3d3	6ecd1231
	fe675eb9	a5e61c01	34e495ba	2a4c3b11	1a861abc
	679f9a37				

$MD_{i=6}:$	1ae75e92	d9a24acc	fe1bc1b6	abe0b643	76efbb19
	cc49fa08	fbf3bc17	724fb774	5045e826	daa4f0de
	fca7adcf	165561a4			

The first few message digests, MD_j , that are the output of the routine found in Figure 1 are:

$MD_{j=0}:$	ce44d7d6	3ae0c914	82998cf6	62a51ec8	0bf6fc68
	661a3c57	f8756611	2bd635a7	43ea904d	eb7d7a42
	ac808cab	e697f38f			

$MD_{j=1}:$	f9c6d261	881fee41	acd39e67	aa8d0bad	507c7363
	eb67e2b8	1f45759f	9c0fd7b5	03df1a0b	9e80bde7
	bc333d75	b804197d			

$MD_{j=2}:$	d96512d8	c9f4a7a4	967a366c	01c6fd97	384225b5
	8343a882	64847c18	e4ef8ab7	aee4765f	fbf3e30b
	d485d363	8a01418f			

$MD_{j=3}:$	0ca76bd0	813af150	9e170907	a9600593	8bc98562
	8290b25f	ef73cf6f	ad68ddba	0ac8920c	94e05416
	07b0915a	7b4457f7			

Appendix E Sample Values for SHA-512 Tests

Each example contains the length of the sample message that is to be hashed, the hex representation of the message, *M*, and the message digest, *MD*, of the message using SHA-512. For bit-oriented messages, the message is in the most significant digits of the hex representation. In Example 1 below, the binary representation of the 5-bit message C8 is 11001.

E.1 Examples Of The Short Messages Test for SHA-512

Example 1:

Length: 5
M: b0
MD: d4ee29a9 e9098544 6b913cf1 d1376c83 6f4be2c1
cf3cada0 720a6bf4 857d886a 7ecb3c4e 4c0fa8c7
f95214e4 1dc1b0d2 1b22a84c c03bf8ce 4845f34d
d5bdbad4

Example 2:

Length: 8
M: d0
MD: 99922029 38e882e7 3e20f6b6 9e68a0a7 14909042
3d93c81b ab3f2167 8d4aceee e50e4e8c afada4c8
5a54ea83 06826c4a d6e74cec e9631bfa 8a549b4a
b3fbba15

Example 3:

Length: 123
M: 08ecb52e bae1f742 2db62bcd 54267080
MD: ed8dc78e 8b01b697 50053dbb 7a0a9eda 0fb9e9d2
92b1ed71 5e80a7fe 290a4e16 664fd913 e8585440
0c5af05e 6dad316b 7359b43e 64f8bec3 c1f23711
9986bbb6

Example 4:

Length: 128
M: 8d4e3c0e 38891914 91816e9d 98bff0a0
MD: cb0b67a4 b8712cd7 3c9aabc0 b199e926 9b20844a
fb75acbd d1c153c9 828924c3 ddedaafe 669c5fdd

0bc66f63 0f677398 8213eb1b 16f517ad 0de4b2f0
c95c90f8

E.2 Examples Of The Selected Long Messages Test for SHA-512

Example 1:

Length: 1123

M: 3addec85 593216d1 619aa02d 9756970b fc70ace2
744f7c6b 27881510 28f7b6a2 550fd74a 7e6e69c2
c9b45fc4 54966dc3 1d2e10da 1f95ce02 beb4bf87
65574cbd 6e8337ef 420adc98 c15cb6d5 e4a0241b
a0046d25 0e510231 cac2046c 991606ab 4ee4145b
ee2ff4bb 123aab49 8d9d4479 4f99ccad 89a9a162
1259eda7 0a5b6dd4 bdd87778 c9043b93 84f54906 80

MD: 32ba76fc 30eaa020 8aeb50ff b5af1864 fdbf1790
2a4dc0a6 82c61fce a6d92b78 3267b210 80301837
f59de79c 6b337db2 526f8a0a 510e5e53 cafed435
5fe7c2f1

Example 2:

Length: 1816

M: a55f20c4 11aad132 807a502d 65824e31 a2305432
aa3d06d3 e282a8d8 4e0de1de 6974bf49 5469fc7f
338f8054 d58c26c4 9360c3e8 7af56523 acf6d89d
03e56ff2 f868002b c3e431ed c44df2f0 223d4bb3
b243586e 1a7d9249 36694fcb baf88d95 19e4eb50
a644f8e4 f95eb0ea 95bc4465 c8821aac d2fe15ab
4981164b bb6dc32f 969087a1 45b0d9cc 9c67c22b
76329941 9cc4128b e9a077b3 ace63406 4e6d9928
3513dc06 e7515d0d 73132e9a 0dc6d3b1 f8b246f1
a98a3fc7 2941b1e3 bb2098e8 bf16f268 d64f0b0f
4707fe1e a1a1791b a2f3c0c7 58e5f551 863a96c9
49ad47d7 fb40d2

MD: c665befb 36da189d 78822d10 528cbf3b 12b3eef7
26039909 c1a16a27 0d487193 77966b95 7a878e72
0584779a 62825c18 da26415e 49a7176a 894e7510
fd1451f5

E.3 Examples of The Pseudorandomly Generated Messages Test for SHA-512

A sample seed for this routine is the following string:

Seed: 473ff1b9 b3ffdfa1 26699ac7 ef9e8e78 77730958
24c64255 7c1399d9 8e422044 8dc35b99 bfdd4477
9543924c 1ce93bc5 94153889 5db98826 1b00774b
12272039

The first few messages, M_i , and hashes, MD_i , contained in the inner loop of the routine in Figure 1 are:

$M_{i=3}$: 473ff1b9 b3ffdfa1 26699ac7 ef9e8e78 77730958
24c64255 7c1399d9 8e422044 8dc35b99 bfdd4477
9543924c 1ce93bc5 94153889 5db98826 1b00774b
12272039 473ff1b9 b3ffdfa1 26699ac7 ef9e8e78
77730958 24c64255 7c1399d9 8e422044 8dc35b99
bfdd4477 9543924c 1ce93bc5 94153889 5db98826
1b00774b 12272039 473ff1b9 b3ffdfa1 26699ac7
ef9e8e78 77730958 24c64255 7c1399d9 8e422044
8dc35b99 bfdd4477 9543924c 1ce93bc5 94153889
5db98826 1b00774b 12272039

$MD_{i=3}$: ab96e447 e4a23028 35b06c3e c33da499 72bfef0b
8678068b c5585945 2292eaa f cc0be757 2c2d14a5
2591fa92 357e5897 0f39ebfc d25877ae 1ba5159e
b251d029

$M_{i=4}$: 473ff1b9 b3ffdfa1 26699ac7 ef9e8e78 77730958
24c64255 7c1399d9 8e422044 8dc35b99 bfdd4477
9543924c 1ce93bc5 94153889 5db98826 1b00774b
12272039 473ff1b9 b3ffdfa1 26699ac7 ef9e8e78
77730958 24c64255 7c1399d9 8e422044 8dc35b99
bfdd4477 9543924c 1ce93bc5 94153889 5db98826
1b00774b 12272039 ab96e447 e4a23028 35b06c3e
c33da499 72bfef0b 8678068b c5585945 2292eaa f
cc0be757 2c2d14a5 2591fa92 357e5897 0f39ebfc
d25877ae 1ba5159e b251d029

$MD_{i=4}$: 94b957d0 fa320e59 38fa342a 753b16ae 74a6f3f1
e27e2260 40ab7ce1 1a3ea232 413539d5 dc08a6d0
74673f63 975628d1 30da35fd fce322a8 fe3f63de
44532669

$M_{i=5}$: 473ff1b9 b3ffdfa1 26699ac7 ef9e8e78 77730958
24c64255 7c1399d9 8e422044 8dc35b99 bfdd4477
9543924c 1ce93bc5 94153889 5db98826 1b00774b

	12272039	ab96e447	e4a23028	35b06c3e	c33da499
	72bfef0b	8678068b	c5585945	2292eaa	cc0be757
	2c2d14a5	2591fa92	357e5897	0f39ebfc	d25877ae
	1ba5159e	b251d029	94b957d0	fa320e59	38fa342a
	753b16ae	74a6f3f1	e27e2260	40ab7ce1	1a3ea232
	413539d5	dc08a6d0	74673f63	975628d1	30da35fd
	fce322a8	fe3f63de	44532669		
$MD_{i=5}:$	8d6751b5	554672e2	3219132d	ad6bb041	b650bea9
	35012c41	f488e847	20a1310e	ad9133a1	6109627c
	fe9895f2	4d5fee88	4aa754a3	4c6549e8	d17bd2c6
	83261b43				
$M_{i=6}:$	ab96e447	e4a23028	35b06c3e	c33da499	72bfef0b
	8678068b	c5585945	2292eaa	cc0be757	2c2d14a5
	2591fa92	357e5897	0f39ebfc	d25877ae	1ba5159e
	b251d029	94b957d0	fa320e59	38fa342a	753b16ae
	74a6f3f1	e27e2260	40ab7ce1	1a3ea232	413539d5
	dc08a6d0	74673f63	975628d1	30da35fd	fce322a8
	fe3f63de	44532669	8d6751b5	554672e2	3219132d
	ad6bb041	b650bea9	35012c41	f488e847	20a1310e
	ad9133a1	6109627c	fe9895f2	4d5fee88	4aa754a3
	4c6549e8	d17bd2c6	83261b43		
$MD_{i=6}:$	69a635e9	14950e8e	e15c27db	d833cb87	a4166951
	5049938a	3acf7ef3	a8c6c5ec	e13300b1	0bb02b8d
	fcc7d0bf	1b504d3a	45cc5623	f07d938d	1aa9902e
	beae48ec				

The first few message digests, MD_j , that are the output of the routine found in Figure 1 are:

$MD_{j=0}:$	2fbb1e7e	00f746ba	514fbc8c	421f3679	2ec0e11f
	f5efc378	e1ab0c07	9aa5f0f6	6a1e3edb	aeb4f998
	4be14437	123038a4	52004a55	768c1fd8	eed49e4a
	21bedcd0				
$MD_{j=1}:$	25cbe5a4	f2c7b1d7	ef070117	05d50c62	c5000594
	243eafd1	241fc9f3	d22b5818	4ae2fee3	8e171cf8
	129e2945	9c9bc2ef	461af570	8887315f	15419d8d
	17fe7949				
$MD_{j=2}:$	5b8b1f26	87555ce2	d7182b92	e5c3f6c3	6547da1c
	13dbb9ea	4f73ea4c	bbaf8941	1527906d	35b1b06c
	1b6a8007	d05ec66d	f0a40606	6829eab6	18bde397
	6515aafc				

MD_{j=3}: 46e36b00 7d19876c db0b29ad 074fe3c0 8cdd174d
42169d6a be5a1414 b6e79707 df58776a 98091cf4
31854147 bb6d3c66 d43bfbc1 08fd715b de6aa127
c2b0e79f

Appendix F Sample Data files

The following subsections contain sample input and output files associated with the SHAVS. For sake of simplicity, abbreviated samples of these files are only provided for the SHA-1 algorithm. The files for other algorithms would be identical, with the exception that input data length may vary and the message digest produced would vary.

F.1 Sample *REQUEST* Files

F.1.1 Sample SHA1ShortMsg.req

```
# CAVS 2.2
# "SHA-1 ShortMsg" information for "Demo Product"
# SHA-1 tests are configured for BIT oriented implementations
# Generated on Wed Mar 26 09:58:58 2003
```

```
[L = 20]
```

```
Len = 0
Msg =
```

```
Len = 1
Msg = 00
```

```
Len = 2
Msg = 40
```

```
Len = 3
Msg = c0
```

```
Len = 4
Msg = 20
```

```
Len = 5
Msg = 98
```

```
Len = 6
Msg = cc
```

```
Len = 7
Msg = 38
```

```
Len = 8
Msg = 5e
```

```
Len = 9
Msg = a200
```

```
Len = 10
Msg = 33c0
```

```
.
```

.
.

Len = 510
Msg =
5cef7fe793576809d8c889840c79d1dbbc8e63f63cdf460cf5fa5ec7ff6b9ba3f33b7098fab687
f82a71b39a138c26389435e416f46d77e42d0fe4e68b0edf50

Len = 511
Msg =
306bd95ece33d3b53cd3797625d678a841a4e226d7fcd3aa809e552b2d4881696be4e7c6e60030
572c7e023bb48d242b1fd8e353bdfdb46053401adb1c81cab4

Len = 512
Msg =
9888d0a161f7648325af72f63295daab867eafbce4f2e99027305afed771e4b5fa71e8db2c2c01
f4f2e5f3064c6ddefa89a2b8465f36f9c93bb298f6d6ba3735

F.1.2 Sample SHA1LongMsg.req

CAVS 2.2
"SHA-1 LongMsg" information for "Demo Product"
SHA tests are configured for BIT oriented implementations
Generated on Wed Mar 26 09:58:58 2003

[L = 20]

Len = 611
Msg =
65f932995ba4ce2cb1b4a2e71ae70220aaccec8962dd4499cbd7c887a94eaaa101ea5aabc529b4e
7e43665a5af2cd03fe678ea6a5005bba3b082204c28b9109f469dac92aaab3aa7c11a1b32ae0

Len = 710
Msg =
e41f78c38e15fb4b00e45df1edc40e3467cdcd351a4c0a0185ac4649e91024377e1c331587a85
86cc0a4dfe29e14004c3536d305f5dee0eeb8c2f216c1b8d27375b239f6458e08980badd6d82e9
ee9e007578c0a3b48288d8

Len = 809
Msg =
b9c05687487749a356666bb10aef23d117c5e8e9d6aef99098884e2b3a8ace55facdc285880b8a
ea61a68e9a58ec78ec7599a122039dc84ce5200a6929c40ecee02a81cc2cb7c28d9a98de3fb203
be74cdc09fc927e9c3c635ee660639dbf49813de79a45a00

Len = 908
Msg =
bee29cf48865b3068418e1e7e142dfbb40cf7a650c508ea80a42318c31932f04bb62b7cd7c0753
9973531d6d9f18314813ec5e054d2b2182c43bd302c01421d06effbd26349d534c422cbf046a06
7d26316a6088267f872072968e6db1b00112004016c557329b671a2b2d74ea13ab9ec1d0

Len = 1007
Msg =
1c9f11faf2a0c6f7e932e650f31191b3d9727b1980354a9c6a623f887fd319b40e2e36130f17fc

```
86aba377f4fe0f439d1bb2adab5030150aacf1977abfd1eae3a11987e836af0ebeaf89e63f5467
243a81c2af0eeffffa17735e9f0a78f5e4d99dd484ca2efd0c649ffce7c587f83fc33168ac969e5
0cb6890e34933777e2
```

Len = 1106

Msg =

```
ab37a9811dcc690394b31135bf2deb09595f9e5d58af007d68712bea97c3d35a52b5d7ff90ae15
0c4d0b83763a087cf7b3e45759f1403ef181c93d6af4169ac4d9d3659be8204fad8034c0975446
23df61ad853723465e000816ae0e25304cab27d97bde8debbfed1577ef2074ae8ac84a024e8055
8807b3e5a1a65e90d99217260f434fe8d70cd4f41c00
```

Len = 1205

Msg =

```
2384405f3d67496fcfa8e0e5fdb052299bd043a3883eald93d5ad6d7a53642d43056e81223b467
0632072db95045e76ec6673b85826cba9fb2a01003921e7e4182948b155c46f68d0456ee6e4142
85d5cbae631aa564b7f9ac9974f47172b9f344c6902e9126dc4c701a8dcc77ae16a5d22d212996
2d812f53cb6871e938da339c7561266a5a038b9bdd719b9b918127056dde7c00cff8
```

Len = 1304

Msg =

```
f78f92141bcd170ae89b4fba15ald59f3fd84d223c9251bdacbbae61d05ed115a06a7ce117b7be
ead24421ded9c32592bd57edeae39c39fa1fe8946a84d0cf1f7beead1713e2e0959897347f67c8
0b0400c209815d6b10a683836fd5562a56cab1a28e81b6576654631cf16566b86e3b33a108b053
07c00aff14a768ed7350606a0f85e6a91d396f5b5cbe577f9b38807c7d523d6d792f6ebc24a4ec
f2b3a427cdbbfb
```

.
.
.

Len = 51200

Msg = ...

The message in the 51200 entry is omitted here for brevity.

F.1.3 Sample SHA1Monte.req

```
# CAVS 2.2
# "SHA-1 Monte" information for "Demo Product"
# SHA tests are configured for BIT oriented implementations
# Generated on Wed Mar 26 09:58:58 2003
```

[L = 20]

Seed = d0569cb3665a8a43eb6ea23d75a3c4d2054a0d7d

F.2 Sample FAX Files

F.2.1 Sample SHA1ShortMsg.fax

```
# CAVS 2.2
# "SHA-1 ShortMsg" information for "Demo Product"
# SHA-1 tests are configured for BIT oriented implementations
```

Generated on Wed Mar 26 09:58:58 2003

[L = 20]

Len = 0

Msg =

MD = da39a3ee5e6b4b0d3255bfef95601890afd80709

Len = 1

Msg = 00

MD = bb6b3e18f0115b57925241676f5b1ae88747b08a

Len = 2

Msg = 40

MD = ec6b39952e1a3ec3ab3507185cf756181c84bbe2

Len = 3

Msg = c0

MD = 6f3b55b9054d756109c4c2e7162970783fd38683

Len = 4

Msg = 20

MD = 91c3d1038358bb4e453e2e67946ef40a32b8d102

Len = 5

Msg = 98

MD = 29826b003b906e660eff4027ce98af3531ac75ba

Len = 6

Msg = cc

MD = 1ac92d2abc0d6ea3c096e80e3e1252de01747bc0

Len = 7

Msg = 38

MD = 64191fbdd73e57f30aec609c6f3258524121604f

Len = 8

Msg = 5e

MD = 5e6f80a34a9798cafc6a5db96cc57ba4c4db59c2

Len = 9

Msg = a200

MD = 658506c6238be94b4a259921ea11a04c0064e5a4

Len = 10

Msg = 33c0

MD = b577bb4bb91ca83d464a1562c343533a7fe50672

.

.

.

Len = 511

Msg =

306bd95ece33d3b53cd3797625d678a841a4e226d7fcd3aa809e552b2d4881696be4e7c6e60030
572c7e023bb48d242b1fd8e353bdfdb46053401adb1c81cab4

MD = f5151d5f4bb68b7b878eb5cdb16e8d325dbb5cf2

Len = 512

Msg =

9888d0a161f7648325af72f63295daab867eafbce4f2e99027305afed771e4b5fa71e8db2c2c01
f4f2e5f3064c6ddefa89a2b8465f36f9c93bb298f6d6ba3735

MD = 004f60b04a2e51be10924ac96a69a9f20c47e6ce

F.2.2 Sample SHA1LongMsg.fax

CAVS 2.2

"SHA-1 LongMsg" information for "Demo Product"

SHA tests are configured for BIT oriented implementations

Generated on Wed Mar 26 09:58:58 2003

[L = 20]

Len = 611

Msg =

65f932995ba4ce2cb1b4a2e71ae70220aaccec8962dd4499cbd7c887a94eaaa101ea5aabc529b4e
7e43665a5af2cd03fe678ea6a5005bba3b082204c28b9109f469dac92aaab3aa7c11a1b32ae0

MD = 8c5b2a5ddae5a97fc7f9d85661c672adbf7933d4

Len = 710

Msg =

e41f78c38e15fb4b00e45df1edc40e3467cdcd351a4c0a0185ac4649e91024377e1c331587a85
86cc0a4dfe29e14004c3536d305f5dee0eeb8c2f216c1b8d27375b239f6458e08980badd6d82e9
ee9e007578c0a3b48288d8

MD = 4fddf903c1843162c19a6114eacf407ab9be9de5

Len = 809

Msg =

b9c05687487749a356666bb10aef23d117c5e8e9d6aef99098884e2b3a8ace55facdc285880b8a
ea61a68e9a58ec78ec7599a122039dc84ce5200a6929c40ecee02a81cc2cb7c28d9a98de3fb203
be74cdc09fc927e9c3c635ee660639dbf49813de79a45a00

MD = 1639095becdd1a6056e0ff2e68730fc4d77dde5a

Len = 908

Msg =

bee29cf48865b3068418e1e7e142dfbb40cf7a650c508ea80a42318c31932f04bb62b7cd7c0753
9973531d6d9f18314813ec5e054d2b2182c43bd302c01421d06effbd26349d534c422cbf046a06
7d26316a6088267f872072968e6db1b00112004016c557329b671a2b2d74ea13ab9ec1d0

MD = e0fd0edfc72a87de298ad669eca781e21c2f4b69

Len = 1007

Msg =

1c9f11faf2a0c6f7e932e650f31191b3d9727b1980354a9c6a623f887fd319b40e2e36130f17fc
86aba377f4fe0f439d1bb2adab5030150aacf1977abfd1eae3a11987e836af0ebeaf89e63f5467
243a81c2af0eefffa17735e9f0a78f5e4d99dd484ca2efd0c649ffce7c587f83fc33168ac969e5
0cb6890e34933777e2

MD = cc7ac764006c94bbd7e723b59e4faf11c400538f

Len = 1106

```

Msg =
ab37a9811dcc690394b31135bf2deb09595f9e5d58af007d68712bea97c3d35a52b5d7ff90ae15
0c4d0b83763a087cf7b3e45759f1403ef181c93d6af4169ac4d9d3659be8204fad8034c0975446
23df61ad853723465e000816ae0e25304cab27d97bde8debbfed1577ef2074ae8ac84a024e8055
8807b3e5a1a65e90d99217260f434fe8d70cd4f41c00
MD = 617b0883711762c604cfe17d65031925a6890cf4

Len = 1205
Msg =
2384405f3d67496fcfa8e0e5fdb052299bd043a3883ea1d93d5ad6d7a53642d43056e81223b467
0632072db95045e76ec6673b85826cba9fb2a01003921e7e4182948b155c46f68d0456ee6e4142
85d5cbae631aa564b7f9ac9974f47172b9f344c6902e9126dc4c701a8dcc77ae16a5d22d212996
2d812f53cb6871e938da339c7561266a5a038b9bdd719b9b918127056dde7c00cff8
MD = 26606fc972b80dea994126c925d18fef688f5569

Len = 1304
Msg =
f78f92141bcd170ae89b4fba15a1d59f3fd84d223c9251bdacbbae61d05ed115a06a7ce117b7be
ead24421ded9c32592bd57edeae39c39fa1fe8946a84d0cf1f7beead1713e2e0959897347f67c8
0b0400c209815d6b10a683836fd5562a56cab1a28e81b6576654631cf16566b86e3b33a108b053
07c00aff14a768ed7350606a0f85e6a91d396f5b5cbe577f9b38807c7d523d6d792f6ebc24a4ec
f2b3a427cdbbfb
MD = cb0082c8f197d260991ba6a460e76e202bad27b3
.
.
.
Len = 51200
Msg = ...
MD = 21cb7972cd6758fc716743d01fab7c947e168e1f

```

The message in the 51200 entry is omitted here for brevity.

F.2.3 Sample SHA1Monte.fax

```

# CAVS 2.2
# "SHA-1 Monte" information for "Demo Product"
# SHA tests are configured for BIT oriented implementations
# Generated on Wed Mar 26 09:58:58 2003

```

```
[L = 20]
```

```
Seed = d0569cb3665a8a43eb6ea23d75a3c4d2054a0d7d
```

```
COUNT = 0
MD = e216836819477c7f78e0d843fe4ff1b6d6c14cd4
```

```
COUNT = 1
MD = a2dbc7a5b1c6c0a8bcb7aaa41252a6a7d0690dbc
```

```
COUNT = 2
MD = db1f9050bb863dfef4ce37186044e2eeb17ee013
```

```
COUNT = 3
```



```
MD = 127fdedf43d372a51d5747c48fbffe38ef6cdf7b
.
.
.
COUNT = 98
MD = 1fa936c81d44366c9592a618d140097d4d0555e4

COUNT = 99
MD = 29fc313684e1735f15dc0bc984064fb081dab588
```

F.3 Sample *SAMPLE* Files

F.3.1 Sample SHA1ShortMsg.sam

```
# CAVS 2.2
# "SHA-1 ShortMsg" information for "Demo Product"
# SHA-1 tests are configured for BIT oriented implementations
# Generated on Wed Mar 26 09:58:58 2003

Len = 0
Msg =
MD = ?

Len = 1
Msg = 00
MD = ?

Len = 2
Msg = 40
MD = ?

Len = 3
Msg = c0
MD = ?

Len = 4
Msg = 20
MD = ?

Len = 5
Msg = 98
MD = ?

Len = 6
Msg = cc
MD = ?

Len = 7
Msg = 38
MD = ?

Len = 8
```

```

Msg = 5e
MD = ?

Len = 9
Msg = a200
MD = ?

Len = 10
Msg = 33c0
MD = ?

.
.
.

Len = 511
Msg =
306bd95ece33d3b53cd3797625d678a841a4e226d7fcd3aa809e552b2d4881696be4e7c6e60030
572c7e023bb48d242b1fd8e353bdfdb46053401adb1c81cab4
MD = ?

Len = 512
Msg =
9888d0a161f7648325af72f63295daab867eafbce4f2e99027305afed771e4b5fa71e8db2c2c01
f4f2e5f3064c6ddefa89a2b8465f36f9c93bb298f6d6ba3735
MD = ?

```

F.3.2 Sample SHA1LongMsg.sam

```

# CAVS 2.2
# "SHA-1 LongMsg" information for "Demo Product"
# SHA tests are configured for BIT oriented implementations
# Generated on Wed Mar 26 09:58:58 2003

Len = 611
Msg =
65f932995ba4ce2cb1b4a2e71ae70220aacec8962dd4499cbd7c887a94eaaa101ea5aabc529b4e
7e43665a5af2cd03fe678ea6a5005bba3b082204c28b9109f469dac92aaab3aa7c11a1b32ae0
MD = ?

Len = 710
Msg =
e41f78c38e15fb4b00e45df1edc40e3467cdcd351a4c0a0185ac4649e91024377e1c331587a85
86cc0a4dfe29e14004c3536d305f5dee0eeb8c2f216c1b8d27375b239f6458e08980badd6d82e9
ee9e007578c0a3b48288d8
MD = ?

Len = 809
Msg =
b9c05687487749a356666bb10aef23d117c5e8e9d6aef99098884e2b3a8ace55facdc285880b8a
ea61a68e9a58ec78ec7599a122039dc84ce5200a6929c40ecee02a81cc2cb7c28d9a98de3fb203
be74cdc09fc927e9c3c635ee660639dbf49813de79a45a00

```

MD = ?

Len = 908

Msg =

bee29cf48865b3068418e1e7e142dfbb40cf7a650c508ea80a42318c31932f04bb62b7cd7c0753
9973531d6d9f18314813ec5e054d2b2182c43bd302c01421d06effbd26349d534c422cbf046a06
7d26316a6088267f872072968e6db1b00112004016c557329b671a2b2d74ea13ab9ec1d0

MD = ?

Len = 1007

Msg =

1c9f11faf2a0c6f7e932e650f31191b3d9727b1980354a9c6a623f887fd319b40e2e36130f17fc
86aba377f4fe0f439d1bb2adab5030150aacf1977abfd1eae3a11987e836af0ebeaf89e63f5467
243a81c2af0eefffa17735e9f0a78f5e4d99dd484ca2efd0c649ffce7c587f83fc33168ac969e5
0cb6890e34933777e2

MD = ?

Len = 1106

Msg =

ab37a9811dcc690394b31135bf2deb09595f9e5d58af007d68712bea97c3d35a52b5d7ff90ae15
0c4d0b83763a087cf7b3e45759f1403ef181c93d6af4169ac4d9d3659be8204fad8034c0975446
23df61ad853723465e000816ae0e25304cab27d97bde8debbfed1577ef2074ae8ac84a024e8055
8807b3e5a1a65e90d99217260f434fe8d70cd4f41c00

MD = ?

Len = 1205

Msg =

2384405f3d67496fcfa8e0e5fdb052299bd043a3883ea1d93d5ad6d7a53642d43056e81223b467
0632072db95045e76ec6673b85826cba9fb2a01003921e7e4182948b155c46f68d0456ee6e4142
85d5cbae631aa564b7f9ac9974f47172b9f344c6902e9126dc4c701a8dcc77ae16a5d22d212996
2d812f53cb6871e938da339c7561266a5a038b9bdd719b9b918127056dde7c00cff8

MD = ?

Len = 1304

Msg =

f78f92141bcd170ae89b4fba15a1d59f3fd84d223c9251bdacbbae61d05ed115a06a7ce117b7be
ead24421ded9c32592bd57edeae39c39fa1fe8946a84d0cf1f7beead1713e2e0959897347f67c8
0b0400c209815d6b10a683836fd5562a56cabla28e81b6576654631cf16566b86e3b33a108b053
07c00aff14a768ed7350606a0f85e6a91d396f5b5cbe577f9b38807c7d523d6d792f6ebc24a4ec
f2b3a427cdbbfb

MD = ?

.
.
.

Len = 51200

Msg = ...

MD = ?

The message in the 51200 entry is omitted here for brevity.

F.3.3 Sample SHA1Monte.sam

CAVS 2.2

```
# "SHA-1 Monte" information for "Demo Product"
# SHA tests are configured for BIT oriented implementations
# Generated on Wed Mar 26 09:58:58 2003
```

```
[L = 20]
```

```
Seed = d0569cb3665a8a43eb6ea23d75a3c4d2054a0d7d
COUNT = 0
MD = e216836819477c7f78e0d843fe4ff1b6d6c14cd4
```

```
COUNT = 1
MD = a2dbc7a5b1c6c0a8bcb7aaa41252a6a7d0690dbc
```

```
COUNT = 2
MD = db1f9050bb863dfef4ce37186044e2eeb17ee013
```

```
COUNT = 3
MD = ?
```

```
.
.
.
```

```
COUNT = 98
MD = ?
```

```
COUNT = 99
MD = ?
```

F.4 Sample *RESPONSE* Files

F.4.1 Sample SHA1ShortMsg.rsp

```
# CAVS 2.2
# "SHA-1 ShortMsg" information for "Demo Product"
# SHA-1 tests are configured for BIT oriented implementations
```

```
[L = 20]
```

```
Len = 0
Msg =
MD = da39a3ee5e6b4b0d3255bfef95601890afd80709
```

```
Len = 1
Msg = 00
MD = bb6b3e18f0115b57925241676f5b1ae88747b08a
```

```
Len = 2
Msg = 40
MD = ec6b39952e1a3ec3ab3507185cf756181c84bbe2
```

```
Len = 3
Msg = c0
MD = 6f3b55b9054d756109c4c2e7162970783fd38683
```

```

Len = 4
Msg = 20
MD = 91c3d1038358bb4e453e2e67946ef40a32b8d102

Len = 5
Msg = 98
MD = 29826b003b906e660eff4027ce98af3531ac75ba

Len = 6
Msg = cc
MD = 1ac92d2abc0d6ea3c096e80e3e1252de01747bc0

Len = 7
Msg = 38
MD = 64191fbdd73e57f30aec609c6f3258524121604f

Len = 8
Msg = 5e
MD = 5e6f80a34a9798cafc6a5db96cc57ba4c4db59c2

Len = 9
Msg = a200
MD = 658506c6238be94b4a259921ea11a04c0064e5a4

Len = 10
Msg = 33c0
MD = b577bb4bb91ca83d464a1562c343533a7fe50672
.
.
.
Len = 511
Msg =
306bd95ece33d3b53cd3797625d678a841a4e226d7fcd3aa809e552b2d4881696be4e7c6e60030
572c7e023bb48d242b1fd8e353bdfdb46053401adb1c81cab4
MD = f5151d5f4bb68b7b878eb5cdb16e8d325dbb5cf2

Len = 512
Msg =
9888d0a161f7648325af72f63295daab867eafbce4f2e99027305afed771e4b5fa71e8db2c2c01
f4f2e5f3064c6ddefa89a2b8465f36f9c93bb298f6d6ba3735
MD = 004f60b04a2e51be10924ac96a69a9f20c47e6ce

```

F.2.2 Sample SHA1LongMsg.rsp

```

# CAVS 2.2
# "SHA-1 LongMsg" information for "Demo Product"
# SHA tests are configured for BIT oriented implementations

[L = 20]

Len = 611

```

Msg =
65f932995ba4ce2cb1b4a2e71ae70220aaccec8962dd4499cbd7c887a94eaaa101ea5aabc529b4e
7e43665a5af2cd03fe678ea6a5005bba3b082204c28b9109f469dac92aaab3aa7c11a1b32ae0
MD = 8c5b2a5ddae5a97fc7f9d85661c672adbf7933d4

Len = 710
Msg =
e41f78c38e15fb4b00e45df1edc40e3467cdcd351a4c0a0185ac4649e91024377e1c331587a85
86cc0a4dfe29e14004c3536d305f5dee0eeb8c2f216c1b8d27375b239f6458e08980badd6d82e9
ee9e007578c0a3b48288d8
MD = 4fddf903c1843162c19a6114eacf407ab9be9de5

Len = 809
Msg =
b9c05687487749a356666bb10aef23d117c5e8e9d6aef99098884e2b3a8ace55facdc285880b8a
ea61a68e9a58ec78ec7599a122039dc84ce5200a6929c40ecee02a81cc2cb7c28d9a98de3fb203
be74cdc09fc927e9c3c635ee660639dbf49813de79a45a00
MD = 1639095becdd1a6056e0ff2e68730fc4d77dde5a

Len = 908
Msg =
bee29cf48865b3068418e1e7e142dfbb40cf7a650c508ea80a42318c31932f04bb62b7cd7c0753
9973531d6d9f18314813ec5e054d2b2182c43bd302c01421d06effbd26349d534c422cbf046a06
7d26316a6088267f872072968e6db1b00112004016c557329b671a2b2d74ea13ab9ec1d0
MD = e0fd0edfc72a87de298ad669eca781e21c2f4b69

Len = 1007
Msg =
1c9f11faf2a0c6f7e932e650f31191b3d9727b1980354a9c6a623f887fd319b40e2e36130f17fc
86aba377f4fe0f439d1bb2adab5030150aacf1977abfd1eae3a11987e836af0ebeaf89e63f5467
243a81c2af0eeffffa17735e9f0a78f5e4d99dd484ca2efd0c649ffce7c587f83fc33168ac969e5
0cb6890e34933777e2
MD = cc7ac764006c94bbd7e723b59e4faf11c400538f

Len = 1106
Msg =
ab37a9811dcc690394b31135bf2deb09595f9e5d58af007d68712bea97c3d35a52b5d7ff90ae15
0c4d0b83763a087cf7b3e45759f1403ef181c93d6af4169ac4d9d3659be8204fad8034c0975446
23df61ad853723465e000816ae0e25304cab27d97bde8debbfed1577ef2074ae8ac84a024e8055
8807b3e5a1a65e90d99217260f434fe8d70cd4f41c00
MD = 617b0883711762c604cfe17d65031925a6890cf4

Len = 1205
Msg =
2384405f3d67496fcfa8e0e5fdb052299bd043a3883ea1d93d5ad6d7a53642d43056e81223b467
0632072db95045e76ec6673b85826cba9fb2a01003921e7e4182948b155c46f68d0456ee6e4142
85d5cbae631aa564b7f9ac9974f47172b9f344c6902e9126dc4c701a8dcc77ae16a5d22d212996
2d812f53cb6871e938da339c7561266a5a038b9bdd719b9b918127056dde7c00cff8
MD = 26606fc972b80dea994126c925d18fef688f5569

Len = 1304
Msg =
f78f92141bcd170ae89b4fba15ald59f3fd84d223c9251bdacbbae61d05ed115a06a7ce117b7be
ead24421ded9c32592bd57edeae39c39fa1fe8946a84d0cf1f7beead1713e2e0959897347f67c8

```

0b0400c209815d6b10a683836fd5562a56cab1a28e81b6576654631cf16566b86e3b33a108b053
07c00aff14a768ed7350606a0f85e6a91d396f5b5cbe577f9b38807c7d523d6d792f6ebc24a4ec
f2b3a427cdbbfb
MD = cb0082c8f197d260991ba6a460e76e202bad27b3
.
.
.
Len = 51200
Msg = ...
MD = 21cb7972cd6758fc716743d01fab7c947e168e1f

```

The message in the 51200 entry is omitted here for brevity.

F.2.3 Sample SHA1Monte.rsp

```

# CAVS 2.2
# "SHA-1 Monte" information for "Demo Product"
# SHA tests are configured for BIT oriented implementations

[L = 20]

Seed = d0569cb3665a8a43eb6ea23d75a3c4d2054a0d7d

COUNT = 0
MD = e216836819477c7f78e0d843fe4ff1b6d6c14cd4

COUNT = 1
MD = a2dbc7a5b1c6c0a8bcb7aaa41252a6a7d0690dbc

COUNT = 2
MD = db1f9050bb863dfef4ce37186044e2eeb17ee013

COUNT = 3
MD = 127fdedf43d372a51d5747c48fbffe38ef6cdf7b
.
.
.
COUNT = 98
MD = 1fa936c81d44366c9592a618d140097d4d0555e4

COUNT = 99
MD = 29fc313684e1735f15dc0bc984064fb081dab588

```

Appendix G References

- [1] *Digital Signature Standard (DSS)*, FIPS Publication 186-2 (+Change Notice), National Institute of Standards and Technology, January 2000.
- [2] *Security Requirements for Cryptographic Modules*, FIPS Publication 140-2, National Institute of Standards and Technology, May 2001.